Chenbro
A9671

www.chenbro.com.tw/

Additional Information

Associated Model #s: A9641, A9651, A9661, A9651-7, A9661-7, A9671, A9681, A9691

Options: Hot Swap Drives.
Redundant PSU

Chassis Configuration (as tested with Intel's Server Board STL2)

Model tested: A9671

Fans (qty x size): 5 x 90 mm, 1 x 60 mm

Hard drives: 3 x Seagate* ST328451 LW Cheetah*

Processor: 2 x 1 Ghz Pentium® III FC-PGA

Memory: 256 MB SDRAM

Power Supply: Seasonic SSR-400

RAID: Intel, BOXSRCU31L

Additional Information:

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel
Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850MHz), N440BX, T440BX, STL2

Thermally Compatible with:

L440GX+ (850MHz), N440BX, T440BX, R440L, STL2

CE Testing Performed with:

N440BX, T440BX

Product Information

Model#: A9671

Size (LxWxH in/mm): 22.8x14.6x26.8in/583x370x680mm

5.25" Bays: 12

3.50" Bays: 1 exposed, 8 internal

Fans: 4 x 9cm (12 x 9 cm, 2 x 8 cm, 1 x 6 cm optional)

Power Supply: Dual or Trio Redundant PSU
3 x PS/2 standard PSU

Other Information: SCA HDD Raid module is optional

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.